



HARBOR PLANK PRODUCT SPECIFICATIONS

PRODUCT SPECIFICATIONS	
Style Number	W020L
Style Name	Harbor Plank
Construction	Class III High Performance LVP
Wear Layer Finish	Urethane with Double UV Coating
Wear Layer Thickness	20 mil
Overall Thickness	8mm (5mm WPC/1.5mm IXPE/1.5mm Vinyl top)
Attached Cushion	1.5mm IXPE Cross Linked Polyethylene
FEATURES	
Plank Edge	Square Edge
Texture	Standard Embossing
Plank Size	6" X 48"
Installation	Floating/Uniclic Locking System
TESTING	
Impact Sound Conduction / ASTM E492-09	IIC 62
Sound Transmission Class /ASTM E90-09	STC 52
Slip Resistance / ASTM D2047	0.70 Dry
Dimensional Stability / ASTM F2199	Pass
Residual Indentation / ASTM F1914	Pass
Static Load limit / ASTM F970	Pass
Resistance to Heat / ASTM F1514	Pass
Resistance to Light / ASTM F1515	Pass
Resistance to Chemicals / ASTM F925	Pass
Radiant Flux / ASTM E648	>0.45 watts/cm², NFPA Class I
Smoke Density / ASTM E662	Pass, <450
WARRANTIES	
Lifetime Residential	
10 Year Commercial	
ENVIRONMENTAL	
Indoor Air Quality	GREENGUARD Gold Certified
	FloorScore® Certified